

Rinnai

Product Specifications

Medium Capacity Gas Storage

135 Litres: For all your hot water needs.



Gas Consumption (Mj/h)	17
Weight (Empty)	68
Relief Valve Setting (kPa))	1000
Max water supply without ECV (kPa)	800
Max water supply with ECV (kPa)	680
Expansion Control Valve Setting (kPa – if required)	850
Recommended PLV (kPa – if required)	500
Water Connections	RP 3/4 20mm
Rated Capacity (Litres)	135
Height – Hot Water Outlet	1316
Height – Cold Water Inlet)	328
Height)	1579
Gas Type	NG & LPG
Water Capacity in First Hour (Litres)	209

Features and Performance

- 4.7 Star energy rating*
- First hour delivery capacity – 209 litres
- Vitreous Enamel lined steel tank
- 8 year cylinder warranty
- First hour delivery capacity* - 209 litres
- 4.7 Star energy rating
- Storage capacity – 135 litres
- Vitreous Enamel lined steel tank adds durability for a longer life
- Inbuilt anode protection extends the life of the tank
- Pressure temperature relief valve
- External use only
- Available in Natural and Propane Gas
- Thermostatically controlled with safety temperature shut off for added peace of mind
- 170 litres variant also available
- *45°C temperature rise, 15°C cold supply temperature

Rinnai

