

# Rinnai

## Product Specifications

### Large Capacity Gas Storage

**170 Litre Storage Capacity: Perfect for Australia's biggest households.**



Gas Consumption (Mj/h)	20.5
Weight (Empty)	83
Relief Valve Setting (kPa))	1000
Max water supply without ECV (kPa)	800
Max water supply with ECV (kPa)	680
Expansion Control Valve Setting (kPa – if required)	850
Recommended PLV (kPa – if required)	500
Water Connections	RP 3/4 20mm
Rated Capacity (Litres)	170
Height – Hot Water Outlet	1616
Height – Cold Water Inlet)	403
Height)	1915
Gas Type	NG & LPG
Water Capacity in First Hour (Litres)	257

### Features and Performance

- 4 Star energy rating\*
- First hour delivery capacity – 257 litres
- Vitreous Enamel lined steel tank
- 8 year cylinder warranty
- First hour delivery capacity\* - 257 litres
- 4 Star energy rating
- Storage capacity – 170 litres
- Vitreous enamel lined steel tank adds durability
- Inbuilt anode protection extends the life of the tank
- Pressure temperature relief valve
- External use only
- Available in Natural and Propane Gas
- Thermostatically controlled with safety temperature shut off for added peace of mind
- 135 litre variant also available
- \*45°C temperature rise, 15°C cold supply temperature

**Rinnai**

