

Rinnai

Product Specifications

Hotflo Electric Storage 250L

250 litres: Keeps even the largest families in hot water.



Electrical Supply	AC 240V 50Hz
Tank Diameter	605
Heating Elements Available (kW)	2.4 / 3.6 / 4.8
Weight Empty (kg)	72
Overall Height	1484
Outlet Height	1248
Inlet Height	210
Electrical Connection Height – Lower (mm)	135
Electrical Connection Height – Upper (mm)	985
Relief Valve Setting (kPa)	1000
Expansion Control Valve Setting (kPa)	850
Max inlet pressure (with ECV – kPa)	680
Max inlet pressure (without ECV – kPa)	800
Water Connections	RP 3/4 20mm
Ingress Protection Rating (AS1939)	IPX4
Rated Capacity (Litres)	250

Features and Performance

- Australian Made
- Flexible installation options
- Perfect for larger families
- 10 year cylinder warranty
- Single and Twin Element available
- Itreous Enamel lined steel tank for added durability
- Inbuilt anode protection extends the life of the tank
- Dual handed, allows increased flexibility during installation
- Pressure temperature relief valve included
- Suitable for internal and external use
- Thermostatically controlled with safety temperature shut off for added peace of mind
- Single and Twin element configurations available

Rinnai

